



PHOENIX 3300

The Powerscreen Phoenix 3300 trommel screen is designed to offer unrivalled production throughput and application flexibility. The robust design with optional features such as heavy duty tipping grid or double deck vibrating grid make the Phoenix 3300 the most versatile trommel on the market today. The machine performs equally well in heavy C&D applications as it does in high volume compost production.



✓ APPLICATIONS

RECYCLING



Wood chippings
Top soil
Compost
Green waste
C&D waste

www.powerscreen.com



TECHNICAL HIGHLIGHTS




HUGE PRODUCTIVITY

- The 180° swivel fines conveyor, with a discharge height of 5.89m (19' 3") results in the creation of impressive stockpiles.
- This swivel feature can be controlled via a remote while the machine is in operation, minimising downtime.
- A powerful four wheel drive system with high performance friction grip wheels is used to turn the trommel drum giving operators the ability to run bi-directionally.



VERSATILITY

- Woven mesh or heavy duty punch plate panels can be fitted to the trommel drum ensuring all application requirements are met.
- Highly efficient in C&D applications and high volume compost applications.




SERVICEABILITY & FUEL ECONOMY

- Powerful hydraulics and auto feeder speed control guarantee the machine is always working at its optimum level.
- Low level hydraulics ensure excellent service access.





TECHNICAL SPECIFICATION



1 HOPPER

Capacity: 7.8m³ (10.2yds³)

2 FEED CONVEYOR

1500mm (59") 3 ply plain belt
Variable speed with load sensing & automatic feeder shutdown

3 DRUM

Friction four wheel drum drive system
Length: 9.31m (30' 6")
Diameter: 2.32m (7' 6")
Variable operating angle 4.5° - 6°
Service access doors for maintenance

4 FINES DISCHARGE CONVEYOR

1200mm (47") 3 ply plain belt
Discharge height: 5.89m (19' 3")

5 OVERSIZE CONVEYOR

1200mm (47") 3 ply chevron belt
Discharge height: 4.16m (13' 7")

6 BOGIE

3 axles, 8 studs
Fifth wheel connection
Airbrakes

7 POWER UNIT

Tier 3: CAT C7.1 151kW (202hp)
Tier 4F: CAT C4.4 129kW (173hp)
Fuel tank capacity: 610 L (161 US Gal)

8 COLLECTION CONVEYOR

1500mm (59") 3 ply plain belt,
Fully skirted & sealed
Variable speed control



DIMENSIONS



Total Weight	37,500kg (82,673lbs) depending on options
Transport Length	21.1m (69' 2")
Transport Height	4.1m (13' 6")
Transport Width	3m (9' 10")
Working Length	32.3m (105' 9")
Working Width	15.8m (51' 8")
Working Height	5.9m (19' 4")

Please note: It is the dealers responsibility to ensure the plant is road legal in their region.

GET IN TOUCH

Dungannon
200 Coalisland Road, Dungannon,
Co Tyrone, BT71 4DR, Northern Ireland
Tel: +44 (0) 28 87 718 500
Fax: +44 (0) 28 87 747 231

Louisville
11001 Electron Drive,
Louisville, Kentucky, 40299 USA
Tel: +1 502 736 5200
Fax: +1 502 736 5202



www.powerscreen.com

The material in this document is for information only and is subject to change without notice. Powerscreen assumes no liability resulting from errors or omissions in this document, or from the use of the information contained herein. Due to continual product development we reserve the right to change specifications without notice. Product performance figures given in this brochure are for guidance purposes only, this information does not constitute an expressed or implied warranty or guarantee, but shows test examples provided by Dealers. These results will vary depending on crusher chamber settings, screen media and sizes, feed source and types of material being processed. Photographs are for illustrative purposes only, some or all of the machines in the illustrations may be fitted with optional extras. Please check with your Dealer for details on optional extras. All machines are CE Approved.

Powerscreen® is a registered trademark of Terex GB Limited in the United States of America and many other countries. Copyright 2019 Terex GB Limited. Published and Printed in October 2019.